


Ex-Leuchte Typ 511


II 2GD Ex de tD A IIC T2-T6

T_{max. surf.}

IP65



Ausführung mit Schutzkorb (K)



AUSFÜHRUNGEN:

-20°C ≤ t_a ≤ +40°C

Spannung Eingang	Leuchtmittel	Temperaturklasse	Maximale Oberflächentemperatur T _{max. surf.} (°C)	Gewicht (kg)	Bestell-Nr.
230 V / 50 HZ	HQL 250 W NAV-E 210 W	T5	87	26,00 (K:+1,50) 27,00 (K:+1,50)	AZ-511 HQL250 (K) AZ-511 NAV-E210 (K)
	HQL 400 W NAV-E 350 W	T3	135	27,00 (K:+1,50)	AZ-511 HQL400 (K) AZ-511 NAV-E350 (K)
	HQI-E 250 W NAV-E 250 W	T4	105	26,00 (K:+1,50)	AZ-511 HQI250 (K) AZ-511 NAV-E250 (K)
	NAV-E 400 W	T3	135	27,00 (K:+1,50)	AZ-511 NAV-E400 (K)
	HQI-E 400 W	T3	135	27,00 (K:+1,50)	AZ-511 HQI-E400 (K)
	HCI-TT 150 W NAV-E 150 W	T6	79	25,00 (K:+1,50)	AZ-511 HCI-TT150 (K) AZ-511 NAV-E150 (K)

-20°C ≤ t_a ≤ +55°C

230 V / 50 HZ	HQL 250 W NAV-E 210 W	T4	102	26,00 (K:+1,50) 27,00 (K:+1,50)	AZ-511 HQL250 (K) † AZ-511 NAV-E210 (K) †
	HQL 400 W NAV-E 350 W	T2	150	27,00 (K:+1,50)	AZ-511 HQL400 (K) † AZ-511 NAV-E350 (K) †
	HQI-E 250 W NAV-E 250 W	T3	120	26,00 (K:+1,50)	AZ-511 HQI250 (K) † AZ-511 NAV-E250 (K) †
	NAV-E 400 W	T2	150	27,00 (K:+1,50)	AZ-511 NAV-E400 (K) †
	HQI-E 400 W	T2	150	27,00 (K:+1,50)	AZ-511 HQI-E400 (K) †
	HCI-TT 150 W NAV-E 150 W	T5	94	25,00 (K:+1,50)	AZ-511 HCI-TT150 (K) † AZ-511 NAV-E150 (K) †

-50°C ≤ t_a ≤ +55°C

230 V / 50 HZ	NAV-E 250 W HQI-E 250 W	T3	120	26,00 (K:+1,50)	AZ-511 NAV-E250 (K) Ft AZ-511 HQI-E250 (K) Ft
	NAV-E 400 W	T2	150	27,00 (K:+1,50)	AZ-511 NAV-E400 (K) Ft
	HQI-E 400 W	T2	150	27,00 (K:+1,50)	AZ-511 HQI-E400 (K) Ft

– weitere Ausführungen und Zubehör auf Anfrage / Änderungen und Irrtum vorbehalten –