

60 No. LEDs
high-performance diodes

- minimum consumption
- maximum output



A fine-wire fuse is visible from the outside and protects against overcurrent

VERSIONS:

Voltage	No. of LEDs	Feeder with Plug	Order-Number
24 V / 50 Hz	60	5 m 10 m	QL6024/5 QL6024/10
42 V / 50 Hz	60	5 m 10 m	QL6042/5 QL6042/10
230 V / 50 Hz	60	5 m 10 m	QL6023/5 QL6023/10

— Feeders in INDUSTRIEFLEX® 07 —

SPECIAL FEATURES:

- IP 55 — protected against water jets and dust → SAFE – even for use in wet areas
- protective tube made from transparent polycarbonate, 1.5 mm wall thickness, 50 mm diameter → long service life even when subject to mechanical loads
- rubber handle and end cap with zinc coated steel hanger → the lamp can be held safely in the hand without danger of it slipping out or it can be securely suspended by its hanger
- the 60 LEDs give off a concentrated, white light over an area, without any lateral dazzling effect → ideal for illuminating close up areas, e.g. for checking, repair, or final acceptance work
- very low heat output → no danger of burns to limbs close to or even touching the lamp
- the LEDs are resistant to vibration and have a service life of up to 50,000 hours → the possibility of a sudden total failure of all the diodes can be excluded for all practical purposes. Even at the end of its service life, the light does not completely extinguish. This characteristic is very important to OPERATIONAL SAFETY
- low power consumption, max.12 watts, means that only small, low output transformers are required for operating voltages of 24 V and 42 V → the transformers are light, easily handled and, with their COST SAVINGS, provide good value for money.

– further designs on request / subject to changes and errors –



