



string application PXA

solo PX



DESIGNS:

compact energy-saving tube, plug-in socket GX 24q-3

wattage	input lead with plug	output lead with plug	order no.		
			24 V AC	42 V AC	230 V AC
26 W	5 m	—	PX 2426/5	PX 4226/5	—
32 W	5 m	—	PX 2432/5	PX 4232/5	—
26 W	5 m	0,5 m	PXA 2426/5	PXA 4226/5	—
32 W	5 m	0,5 m	PXA 2432/5	PXA 4232/5	—

1-part compact energy-saving tube and electronic choke, with E27 socket

20 W	5 m	—	—	—	PX 2320/5
20 W	5 m	0,5 m	—	—	PXA 2320/5

long-life bulb, E27 socket

60 W	5 m	—	PX 2460/5	PX 4260/5	PX 2360/5
	5 m	0,5 m	PXA 2460/5	PXA 4260/5	PXA 2360/5

SPECIAL FEATURES:

- lamp in IP 65, hose-proof and dust-proof → SAFE and permanent lighting, even in extremely wet and dusty areas, lowers risks at workplaces
- series connecting of the lamps in numerous variants, e.g.
 - with plug-type or fixed connectors between individual lamps
 - distances and number as required
 → optimum SOLUTIONS can be planned and realised depending on place of use and light requirements
- connection of line cross-sections up to 2x3x6 mm² are possible → unacceptable power losses are avoided. long strings of lights with one feeder SAVE labour costs and material
- wide choice of bulbs in terms of output, voltage and light colour → further details for the individual solution on REQUEST

– other lead lengths and other designs on request / subject to changes and errors –



SPECIFICATIONS AND SPECIAL FEATURES

stainless, sturdy suspension bow



IP 68-threaded joint(s)

impact- and shock-proof polycarbonate enclosure, resistant to oil, acid, alkanes, self-extinguishing

Loss electronic choke with direct light current without stroboscopic effect and non-flicker immediate start.

working frequency: 20 kHz
voltage: 24 V oder 42 V (+/-10 %)
frequency: 50 / 60 Hz
working temperature: -10°C bis +50°C
output: 26 W oder 32 W

lamp socket with twist lock for a safe fit of the energy-saving tubs

compact-energy-saving tube DULUX T/E light colour 21 (white) with bayonet cap GX 24q-3



designs with porcelain E2 socket and long-life bulb



shock- and impact-proof, transparent dome of Macrolon

Dimensions:
diameter max. 161 mm
overall height incl. bow 272 mm



the bulb can be changed without tools too



SPARE PARTS:

transparent dome of Macrolon

bulbs:

compact energy-saving tube 26 W
compact energy-saving tube 32 W

compact energy-saving tube 20 W
230 V, 1-part with electronic choke,
E27 socket

order no.

PX 001

long-life bulb 60 watts matt
in voltage 24 V
in voltage 42 V
in voltage 230 V

PX 026

PX 032

CPX 020

order no.

LL 60/24
LL 60/42
LL 60

Accessories:

magnetic holder with high holding force
and carbine swivel

KX/MAG

– other lead lengths and other designs on request / subject to changes and errors –