



**DESIGNS:**

compact energy-saving tube, plug-in socket GX 24q-5

| wattage | input<br>lead with plug | output<br>lead with connector | 24 V AC           | 42 V AC           | 230 V AC            |
|---------|-------------------------|-------------------------------|-------------------|-------------------|---------------------|
|         |                         |                               | order no.         | order no.         | order no.           |
| 42 W    | 5 m                     | —                             | <b>CX 2442/5</b>  | <b>CX 4242/5</b>  | * <b>CX 2342/5</b>  |
| 57 W    | 5 m                     | —                             | <b>CX 2457/5</b>  | <b>CX 4257/5</b>  | —                   |
| 42 W    | 5 m                     | 0,5 m                         | <b>CXA 2442/5</b> | <b>CXA 4242/5</b> | * <b>CXA 2342/5</b> |
| 57 W    | 5 m                     | 0,5 m                         | <b>CXA 2457/5</b> | <b>CXA 4257/5</b> | —                   |

separate electronic choke with E27 socket, compact energy-saving tube, plug-in socket G24q1

|      |     |       |   |   |                   |
|------|-----|-------|---|---|-------------------|
| 13 W | 5 m | —     | — | — | <b>CX 2313/5</b>  |
| 13 W | 5 m | 0,5 m | — | — | <b>CXA 2313/5</b> |

1-part compact energy-saving tube and electronic choke, with E27 socket

|      |     |       |   |   |                   |
|------|-----|-------|---|---|-------------------|
| 20 W | 5 m | —     | — | — | <b>CX 2320/5</b>  |
|      | 5 m | 0,5 m | — | — | <b>CXA 2320/5</b> |

long-life bulb, E27 socket

|       |     |       |                   |                   |                   |
|-------|-----|-------|-------------------|-------------------|-------------------|
| 150 W | 5 m | —     | <b>CX 2415/5</b>  | <b>CX 4215/5</b>  | <b>CX 2315/5</b>  |
|       | 5 m | 0,5 m | <b>CXA 2415/5</b> | <b>CXA 4215/5</b> | <b>CXA 2315/5</b> |

**SPECIAL FEATURES:**

- lamp in IP 65, hose-proof and dust-proof → SAFE and permanent lighting, even in extremely wet and dusty areas, lowers risks at workplaces
- further special features see Interconnecting lamp PX PERFEKT page 7.21.3

– other lead lengths and other designs on request / subject to changes and errors –



**SPECIFICATIONS AND SPECIAL FEATURES**

stainless, sturdy suspension bow

IP 68-threaded joint(s)

Loss electronic choke with direct light current without stroboscopic effect and non-flicker immediate start.

working frequency: 20 kHz  
voltage: 24 V oder 42 V (+/-10 %)  
frequency: 50 / 60 Hz  
working temperature: -10°C bis +50°C  
output: 26 W oder 32 W

impact- and shock-proof polycarbonate enclosure, resistant to oil, acid, alkans, self-extinguishing

lamp socket with twist lock for a safe fit of the energy-saving tubs

large Neoprene ring pressed into a guide groove, keeps out hose water

mirror finish metal reflector

compact-energy-saving tube DULUX T/E  
light colour 21 (white) with bayonet cap GX 24q-5

designs with porcelain E2 socket and long-life bulb

shock- and impact-proof, transparent dome of Macrolon

lock ring of polycarbonate with 3 knurled screws of INOX steel, captive, with spring pressure mechanism

**Dimensions:**  
diameter max. 161 mm  
overall height incl. bow 272 mm

the bulb can be changed without tools too



**SPARE PARTS :**

transparent dome of Macrolon  
lock ring, complete  
neoprene ring

order no.

**GX 02**  
**CX 001**  
**CX 002**

bulbs:  
compact energy-saving tube 42 W  
compact energy-saving tube 57 W

**CX 042**  
**CX 057**

adapter with ignition electronics 230 V / 13 W,  
base with E27 thread, socket G24q1  
compact energy-saving tube 13 W

**CX 003**  
**CX 013**

compact energy-saving tube 20 W 230 V,  
1-part with electronic choke, E27 socket  
long-life bulb 150 watts matt  
in voltage 24 V  
in voltage 42 V  
in voltage 230 V

order no.

**CPX 020**  
**LL 150/24**  
**LL 150/42**  
**LL 150**

**Accessories:**  
magnetic holder with high holding force  
and carbine swivel

**KX/MAG**

- other lead lengths and other designs on request / subject to changes and errors -