



## FEATURES AND QUALITIES:

- stainless steel construction
- pole diameters of 50/45/40/35 mm, thickness 1.5 mm
- 3 blocking systems of aluminum with all-around clamping, captive grips •
- THW tripod with integrated QUAD rings to prevent water penetrating the blocking systems •
- support tube of square profile tubing with a special folding mechanism •
- stabilizing leg adjustable with push slider, captive grip •
- shock absorber: pneumatic design for air-cushioned lowering •
- IFW tripod equipped with hand protection gap on telescopic parts
- connection end with ø 30 mm DIN pins as per DIN 14640
- supporting legs with ø 80 mm base plates and pins
- fastening set, anchoring set and double cross-bars optional

## MODELS:

Туре	Frame*	Î	Å	Å	$\odot$	$\overline{\Lambda}$	K.	Order No.
THW	SS	145 cm	480 cm	145 cm	160 cm	20.0 kg	18.0 kg	TW7840SA
IFW	SS	145 cm	480 cm	145 cm	160 cm	20.0 kg	18.0 kg	TV7830SA

\*Material: SS = Stainless steel



When folded the tripod has a length of 145 cm and is held together by the lashing strap delivered with the tripod.



The triangular fastening plate for attaching the caribiner hooks of the guy ropes is attached directly under the DIN pin.



For secure positioning, possible unevenness can be leveled out with the help of the leveling elements.

- other models on request / subject to modification and errors -



E-Mail: info@elspro.de http://www.elspro.de





THW - article number: 6230T22397

## **COMPONENTS AND ACCESSORIES**

Order No.

## **ELSPRO – FASTENING SET**

TW-AS750X3

**TW-EA400** 

- consisting of each 3 x:
- 7.5 m polyamide fastening rope Ø 4 mm as per DIN EN ISO 1140, color: white
- 1 carabiner as per DIN 5299–C80
- 1 ring, high-gloss galvanized, A 40 x 5, as per DIN 5296
- 1 rope thimble as per DIN 6899
- 2 wire rope clamps, oval
- 1 adjustment element, galvanized, for adjusting the rope length



THW - article number: 6230T22398



Cross bar including basic mounting support and DIN pins

**ELSPRO - Ground Anchoring Set** 3 x ground anchors:

400 mm long, hot-dip galvanized

- basic mounting bracket/support including star grip for attaching to the tripod
- 2 x stainless steel DIN pins ø 30 mm
- 1 x stainless steel C-profile rail

**ELSPRO - Double Cross Bars** Double cross bars consisting of:

- Length 450 mm	TV045
- Length 600 mm	TV060