swivelling wall tripod with long neck

Boom systems are helpful in lighting hard-to-access areas professionally. They are used above all in places where there would be no space or stable support for tripod legs.

The boom systems are available in two models:

- with stable wall mounting (type W)
- with flexible clamp mounting (type C) for securely attachment to tubes and bars, for example:
 - minimum diameter: 12 mm
 - maximum diameter: 45 mm

FEATURES AND QUALITIES:

- stable models in black anodized aluminum
- swivel and tilt angle: 180°
- Iockable swivel and tilt angle
- delivery including DIN pins ø 30 mm



MODELS:

Туре	Frame*	Mounting	Minimum length and load capacity	Maximum length and load capacity	Order No.
GIRAFFE W01	AL	wall mounting	1.20 m / 8.0 kg	2.10 m / 4.0 kg	TV7390W
GIRAFFE W02	AL	wall mounting	0.70 m / 10.0 kg	1.25 m / 5.0 kg	TV7391W
GIRAFFE C01	AL	clamp mounting	1.20 m / 8.0 kg	2.10 m / 4.0 kg	TV7390C
GIRAFFE C02	AL	clamp mounting	0.70 m / 10.0 kg	1.25 m / 5.0 kg	TV7391C

*Material: AL = aluminum. black anodized





GIRAFFE Type C

- other models on request / subject to modification and errors -

E-Mail: info@elspro.de ≞ +49(0)2103/9710-80 http://www.elspro.de

