

Configuration Example

Mobile Safety Distribution Boxes



Solid Rubber Housing
Series
FREIBURG

Number	Output Sockets	Fuse Protection	Residual Current Circuit Breaker	RCD Type A	Cable with Plug	Order No.
--------	----------------	-----------------	----------------------------------	------------	-----------------	-----------

8 sockets with earthing contact	8 B-Aut. 1p.	40A/30mA/4p.	3m	CEE 400V 32A 5p.	1453001
9 sockets with earthing contact	—	40A/30mA/4p.	3m	CEE 400V 16A 5p.	1411004



2 CEE 400V 16A 5p. and 4 sockets with earthing contact	2 C-Aut. 3p. 2 B-Aut. 1p.	40A/30mA/4p.	3m	CEE 400V 32A 5p.	1453113
1 CEE 400V 32A 5p. and 2 CEE 400V 16A 5p. and 3 sockets with earthing contact	— 2 C-Aut. 3p. 2 B-Aut. 1p.	40A/30mA/4p.	3m	CEE 400V 32A 5p.	1453310



2 CEE 400V 32A 5p. and 1 CEE 400V 16A 5p. and 3 sockets with earthing contact	2 C-Aut. 3p. 1 C-Aut. 3p. 3 B-Aut. 1p.	63A/30mA/4p.	3m	CEE 400V 63A 5p.	1456346
2 CEE 400V 32A 5p. and 1 CEE 400V 16A 5p. and 4 sockets with earthing contact	— 1 Neokit 3p. 4 Neokit 1p.	40A/30mA/4p.	3m	CEE 400V 32A 5p.	1433310



1 CEE 400V 63A 5p. and 1 CEE 400V 32A 5p. and 1 CEE 400V 16A 5p. and 3 sockets with earthing contact	— 1 C-Aut. 3p. 1 C-Aut. 3p. 2 B-Aut. 1p.	63A/30mA/4p.	3m	CEE 400V 63A 5p.	1456612
--	---	--------------	----	------------------	----------------



– other cable lengths and models on request / subject to modification and errors –

stackable versions on request



Fig. 1



Fig. 2

with internal protective device

with colored lid on request



SPECIAL FEATURES:

- hinge with a solid V2A axis
 - 2 M6 screws made of V2A steel, undetachable, guaranteeing secure and easy closure of the distribution box
 - four sturdy feet provide 30 mm floor clearance and a firm foothold (Fig. 1)
 - protection guards are arranged clearly under the lid, protecting against accidental contact (Fig. 2)
 - on request: 2 star-handle screws, undetachable, for opening the box without tools (Fig. 3)
 - designed to accommodate a closing mechanism (Fig. 3)
 - inclined and overhanging lid that is also furnished with a rain deflector spanning all sides
 - large, stable carrying handle
 - the inside of the distribution box also displays a clear, maintenance-friendly design
- lid functionality is guaranteed, even when implemented under rough conditions and high mechanical strain
 - protection guards cannot be tampered with by unauthorized persons - SAFETY
 - perfectly suited to nearly all ground conditions
 - live parts cannot be touched, facilitating easy and safe operation
 - trained personnel have quick access to the safety devices - TIME SAVINGS
 - only key holders can open the distribution box
 - rain and spray water cannot build up on the housing
 - thanks to a special shape (recessed grip), the distribution box is comfortable and safe to carry during transport
 - maintenance work can be carried out quickly and simply - COST SAVINGS



with colored engraving on request



Fig. 3

with star-handle screws on request

with a padlock on request