

ELSPRO INDUSTRIESTATIV Typ THW

FEATURES AND QUALITIES:

- stainless steel construction
- pole diameters of 50/45/40/35 mm, thickness 1.5 mm
- 3 blocking systems of aluminum with all-around clamping, captive grips and with integrated QUAD rings to prevent water penetrating the blocking systems
- support tube of square profile tubing with a special folding mechanism
- stabilizing leg adjustable with push slider, captive grip
- shock absorber: pneumatic design for air-cushioned lowering
- connection end with ø 30 mm DIN pins as per DIN 14640
- supporting legs with ø 80 mm base plates and pins
- fastening set, anchoring set and double cross-bars optional



AUSFÜHRUNGEN:

| Type | Frame* | | | | | | | Order No. | | | | |
|------|--------|--|--------|--|--------|--|--------|-----------|--------|---------|---------|-----------------|
| THW | SS | | 145 cm | | 480 cm | | 145 cm | | 160 cm | 20,0 kg | 18,0 kg | TW7840SA |

*Material: **SS** = Stainless steel



When folded the tripod has a length of 145 cm and is held together by the lashing strap delivered with the tripod.



The triangular fastening plate for attaching the carabiner hooks of the guy ropes is attached directly under the DIN pin.



For secure positioning, possible unevenness can be leveled out with the help of the leveling elements.

– other models on request / subject to modification and errors –

ELSPRO Industrial Tripod Type THW



THW – article number: 6230T22397

COMPONENTS AND ACCESSORIES

Order No.

ELSPRO – FASTENING SET

consisting of each 3 x:

- 7.5 m polyamide – fastening rope Ø 4 mm as per DIN EN ISO 1140, color: white
- 1 carabiner as per DIN 5299–C80
- 1 ring, high-gloss galvanized, A 40 x 5, as per DIN 5296
- 1 rope thimble as per DIN 6899
- 2 wire rope clamps, oval
- 1 adjustment element, galvanized, for adjusting the rope length

TW-AS750X3



THW – article number: 6230T22398

ELSPRO - Ground Anchoring Set

TW-EA400

3 x ground anchors:

- 400 mm long, hot-dip galvanized



Cross bar including basic mounting support and DIN pins

ELSPRO - Double Cross Bars

Double cross bars consisting of:

- basic mounting bracket/support including star grip for attaching to the tripod
- 2 x stainless steel DIN pins ø 30 mm
- 1 x stainless steel C-profile rail

- Length 450 mm

TV045

- Length 600 mm

TV060