

ELSPRO Industrial Tripods BETA Series







more than a tripod

FEATURES AND QUALITIES:

- models in black-anodized aluminum or galvanized steel
- tube diameters: 45/38/32 mm
- CLT-locking device (uniform all-around clamping of the tripod tubes)
- standing tube of square profile tubing with folding mechanism
- shock absorber: pneumatic design for air-cushioned lowering
- equipped with hand protection gap on telescopic parts
- anchoring mechanism optional
- connecting end with \varnothing 30 mm DIN pins
- including aluminum foot set with groove profile in black



MODELS:

Type	Frame*							Order No.
BETA 1	AL	176 cm	412 cm	150 cm	176 cm	22/30 kg	8.6 kg	TV7501SA
BETA 1	CS	176 cm	412 cm	150 cm	176 cm	27/35 kg	16.8 kg	TV7502SA
BETA 2	AL	140 cm	332 cm	123 cm	128 cm	24/32 kg	7.3 kg	TV7511SA
BETA 2	CS	140 cm	332 cm	123 cm	128 cm	29/37 kg	13.3 kg	TV7512SA
BETA 3	AL	114 cm	252 cm	96 cm	114 cm	26/34 kg	6.5 kg	TV7521SA
BETA 3	CS	114 cm	252 cm	96 cm	114 cm	31/39 kg	10.8 kg	TV7522SA

* Material: **AL** = aluminum, black anodized; **CS** = steel, black galvanized; **CSW** = steel, white chrome-plated (on request)

** The maximum permissible load capacity decreases depending on the height used: max. load capacity at max./min. extended tripod.

Components and Accessories:

Order No.

Wheel set (\varnothing 100 mm) with double brake and adapter in black aluminum

for ELSPRO industrial tripod BETA 1 + 2
for ELSPRO industrial tripod BETA 3

TV7505
TV7506



It is possible to attach up to 4 panel lights to the BETA industrial tripod without impairing the standing stability.

The shock absorber provides additional protection since it slows down the lowering of the tripod.



Fastening Set consisting of:

- triangular fastening plate V2A
- 3x fastening rope
- 3x ground anchors

Order-No.

ABSPANNSET.UNI

— other models on request / subject to modification and errors —