

ELSPRO Industrial Tripods BETA Series







more than a tripod

FEATURES AND QUALITIES:

- models in black-anodized aluminum
- tube diameters: 50/45/40 mm
- standing tube of square profile tubing with folding mechanism
- protected leveling leg made of V2A stainless steel
- shock absorber: pneumatic design for air-cushioned lowering
- equipped with hand protection gap on telescopic parts
- anchoring mechanism optional
- Connection end with Ø 30 mm DIN pin or, alternatively, extendable Ø 16 mm DIN pin
- including aluminum foot set with groove profile



MODELS:

Type	Frame*							Order No.
BETA 1	AL	176 cm	412 cm	150 cm	176 cm	30.0 kg	9.4 kg	TV7507SA
BETA 2	AL	140 cm	332 cm	123 cm	128 cm	30.0 kg	7.3 kg	TV7517SA
BETA 3	AL	114 cm	252 cm	96 cm	114 cm	30.0 kg	7.0 kg	TV7527SA

*Material: AL = Aluminium

COMPONENTS and ACCESSORIES:

Wheel set with double brake and adapter in black aluminium

for ELSPRO industrial tripod BETA 1 - 3

Order No.



TV7577



Leveling leg for stable positioning on uneven ground



Ø 30 mm DIN pin (plug-in type) or alternatively integrated, extendable Ø 16 mm DIN pin



Fastening Set consisting of:

- triangular fastening plate V2A
- 3x fastening rope
- 3x ground anchors

Order-No.

ABSPANNSET.UNI

– other models on request / subject to modification and errors –