

ELSPRO Industrial Tripods DELTA Series









robust in use and modern in design

FEATURES AND QUALITIES:

- models in black anodized aluminum or galvanized steel
- tube diameters: 35/30/25 mm
- CLT locking system (uniform all-around clamping of the tripod tubes)
- supporting legs with folding mechanism and fiberglass sealing plugs
- protected brass leveling leg (DELTA 1)
- shock absorber: pneumatic design for air-cushioned lowering
- equipped with hand protection gap on telescopic parts
- anchoring mechanism optional
- connecting end with \varnothing 30 mm DIN pins

MODELS:

Type	Frame*							Order No.
DELTA 1	CS	135 cm	380 cm	137 cm	130 cm	12/25 kg	7.3 kg	TV7702SA
DELTA 5	AL	102 cm	285 cm	104 cm	109 cm	13/17 kg	3.3 kg	TV7741SA
DELTA 7	AL	83 cm	222 cm	85 cm	99 cm	15/20 kg	2.8 kg	TV7761SA
DELTA 7	CS	83 cm	222 cm	85 cm	99 cm	22/30 kg	4.5 kg	TV7762SA

* Material: **AL** = aluminum, black anodized; **CS** = steel, black galvanized; **CSW** = steel, white chrome-plated (on request)

** The maximum permissible load capacity decreases depending on the height used: max. load capacity at max./min. extended tripod.

Components and Accessories:

Wheel set (\varnothing 80 mm) with double brake and black aluminum adapter

for ELSPRO industrial tripod DELTA 1
for ELSPRO industrial tripod DELTA 5
for ELSPRO industrial tripod DELTA 7

Order No.

TV7705
TV7706
TV7707



Example for use:
industrial tripod DELTA with tilt joint
and panel light type QV72



Fastening Set consisting of:

- triangular fastening plate V2A
- 3x fastening rope
- 3x ground anchors

Order-No.

ABSPANNSET.UNI

— other models on request / subject to modification and errors —