

ELSPRO Industrial Tripod DELTA Series









DELTA 9

robust in use and modern in design

FEATURES AND QUALITIES:

- models in black anodized aluminum
- tube diameters: 35/30/25 mm
- 2 blocking systems with surface clamping
- supporting legs with folding mechanism
- shock absorber: pneumatic design for air-cushioned lowering
- pinch protection thanks to integrated rubber rings on the extendable segments
- connecting end with Ø 30 mm DIN pins

MODELS:

Type	Frame*							Order No.
DELTA 8	AL	90 cm	220 cm	90 cm	100 cm	15 / 20 kg	2.8 kg	TV7722SA
DELTA 9	AL	102 cm	270 cm	102 cm	110 cm	13 / 17 kg	3.3 kg	TV7727SA
DELTA 4	AL	105 cm	360 cm	125 cm	110 cm	10 / 13 kg	3.6 kg	TV7731

\* Material: **AL** = aluminum, black

\*\* The maximum permissible load capacity decreases depending on the height used: max. load capacity at max./min. extended tripod.

FEATURES and QUALITIES:

Wheel set (ø 80 mm) with double brake and black aluminum adapter

for ELSPRO industrial tripod DELTA 8  
for ELSPRO industrial tripod DELTA 9

Order No.

TV7728  
TV7729

Example for use:  
industrial tripod DELTA with  
tilt joint TV001/5  
and panel light type QVL60



DELTA 8 with wheel set TV7728

- other models on request / subject to modification and errors -