

LED Trough Light EXTRA-P



MODELS:

Voltage	Power	Luminous flux	T _a max	Dimensions	Weight	Order no.
220-240 V AC 50/60 Hz, 220-240 V DC	8.5 W	1,382 lm	≤+50°C	670 x 155 x 105 mm	1.84 kg	EXTRA-P-64163
	14.4 W	2,249 lm			1.64 kg	EXTRA-P-64164
	28.9 W	4,478 lm			1.98 kg	EXTRA-P-64165
	16.9 W	2,765 lm	≤+60°C	1,280 x 155 x 105 mm	3.25 kg	EXTRA-P-64253
	26.4 W	4,159 lm	≤+50°C			EXTRA-P-64255
	52.9 W	8,280 lm	≤+45°C			EXTRA-P-64257
	19.7 W	3,267 lm	≤+60°C	1,580 x 155 x 105 mm	3.99 kg	EXTRA-P-64493
	39.7 W	6,239 lm	≤+50°C		4.02 kg	EXTRA-P-64495
	64.1 W	10,230 lm	≤+45°C		4.12 kg	EXTRA-P-64497
	85.1 W	13,797 lm	≤+35°C		3.70 kg	EXTRA-P-64498
	103.6 W	16,446 lm			4.12 kg	EXTRA-P-64499


- Versions with DALI-2 control and 3-hour battery emergency lighting function available on request -

SPECIAL FEATURES:


- High-power LED with up to 166 lm/W.
- Light colour 4,000 K.
- CRI +80
- Power factor 0.98
- Lifetime L90B50 Ta 25- up to 110,000 hours
- Polycarbonate housing and cover, stainless steel diffuser clips
- Includes two stainless steel brackets for wall and ceiling mounting as standard
- Cable gland M20 (alternatively M25)
- Protection class 1
- IP 66 / IP 67
- Ambient temperature: -30°C ≤ T_a ≤ see table
- Optionally with single-phase or three-phase through-wiring
- High light output
- Neutral white (5,000 K - 6,500 K on request)
- High colour rendering index
- Proven longevity
- IK10, resistant to mechanical stress (protection against impacts with an impact energy of up to 20 joules)
- Easy installation on the ceiling or wall of the room to be illuminated
- Line diameter of 7-13 mm
- Dust-tight and protected against water jets
- Use at elevated ambient temperatures and large temperature fluctuations

- Further models on request / subject to change and error -


LED Trough Light EXTRA-P



LIGHT EMISSION:




DIMENSIONS:



ACCESSORIES:



Wire hanger set (2 pcs)
for chain suspension
(without chain)
EXV005/SET



Set of 45° metal
brackets for wall
mounting (2 pcs.)
EXV006



Self-locking cable
suspension (2 pcs. à
3 m)
EXV007



Clamp set (2 pcs.) for
mounting on a boom
with Ø 50 mm
EXV008/SET

– Further models on request / subject to change and error –