



MODELS:

Voltage	Output	Luminous flux LED-Panel	Protection class	Cable with Plug	Outlets Sockets	Weight without Cable	Order No.
230 V / 50 Hz	29 W	3.100 lm	IP 55	5 m 10 m	- without -	1,2 kg	QVL2325/5 QVL2325/10
			IP 54	5 m 10 m	2 earthing contact	1,5 kg	QVL2325/5/02 QVL2325/10/02

- dimensions (WxHxD): 215 x 250 x 155 mm
- limited weight
- LED panel with highly efficient SMD LEDs
- housing made of impact-resistant polycarbonate, edge protector of soft, thermoplastic elastomer
- incl. robust switch on the lamp
- low heat development

- limited space required, flat and compact form
- easy and trouble-free handling while in use
- high light output with low energy consumption, COST SAVINGS
- strongly suitable for mobile use on building and construction sites
- can be switched on and off directly at the workplace
- no burns when touched, SAFETY

– other cable lengths and models on request / subject to modification and errors –

ACCESSORIES:

	Order No.
- Tripod type DELTA 4 with Ø 30 mm DIN pins • black aluminium • height when folded: 105 cm • maximum height when set up: 360 cm • minimum height when set up: 125 cm • diameter of the maximum footprint: 110 cm • max. load capacity: ca. 13 kg • tripod weight: ca. 2.5 kg • completely preassembled	TV7731
- luminaire bracket + U-stand adapter	QVL2210
- luminaire bracket + female spigot adapter	QVL2220



Tripod type TV7731



luminaire bracket + U-stand adapter QVL2210



luminaire bracket + female spigot adapter QVL2220

– other tripods and cross bars are found starting on page 13.1 / subject to modification and errors –