



MODELS:



LED light source with E27 base

Output	Lumen	Input Cable with plug	Output Cable with Coupling	Order No.	Order No.	Order No.
				24 V AC	42 V AC	230 V AC
10 W	1.000	5 m	-	PXL2410/5	PXL4210/5	PXL2310/5
		5 m	0,5 m	PXLA2410/5	PXLA4210/5	PXLA2310/5

SPECIAL FEATURES:

- lamp in IP 65, sprayproof and dust-tight → SAFE and permanent illumination, also in extremely wet and dusty areas, reduces dangers in the workplace
- serial connection of the lamps in many variations, e.g., with connector system or fixed connections between the individual lamps, distance and number as required → optimal SOLUTIONS according to place of use and lighting needs are planned and produced
- connection with cable cross-sections of up to max. 14 mm are possible → impermissible drops in voltage are avoided; long series of lights with one power feed SAVE labor costs and materials

– other models on request / subject to modification and errors –

CHARACTERISTICS AND SPECIAL FEATURES

rustproof, stable suspension bracket

Fall- and impact-resistant polycarbonate housing, resistant to oil, acids, and alkaline solutions, self-extinguishing

Dimensions:

Diameter max. 161 mm

Total height incl. bracket 272 mm

Shock- and impact-resistant clear cover of Makrolon with practical threaded closure

Models with porcelain socket E27 and LED light source

Light source replacement without tools

REPLACEMENT PARTS:

Clear cover of Makrolon

LED-Leuchtmittel 10 W
 24 V, E27 base, 6.000 K
 42 V, E27 base, 6.000 K
 230 V, E27 base, 6.000 K

Order No.

PX001

LM.LED10/24B
LM.LED10/42B
LM.LED10/230B

Accessories:

Magnetic holder with strong gripping force and carabiner hook

Order No.

KX/MAG

– other models on request / subject to modification and errors –