



Chain Application CXLA

solo CXL

**MODELS:**



LED module

Output	Lumen	Input Cable with plug	Output Cable with Coupling	Order No. 24 V AC	Order No. 42 V AC	Order No. 230 V AC
		5 m	-	<b>CXL2420/5</b>	<b>CXL4220/5</b>	<b>CXL2320/5</b>
20 W	2.320	5 m	0,5 m	<b>CXLA2420/5</b>	<b>CXLA4220/5</b>	<b>CXLA2320/5</b>

**BESONDERHEITEN:**

- lamp in IP 65, sprayproof and dust-tight → SAFE and permanent illumination, also in extremely wet and dusty areas, reduces dangers in the workplace
- serial connection of the lamps in many variations, e.g., with connector system or fixed connections between the individual lamps, distance and number as required → optimal SOLUTIONS according to place of use and lighting needs are planned and produced
- connection with cable cross-sections of up to max. 14 mm<sup>2</sup> are possible → impermissible drops in voltage are avoided; long series of lights with one power feed SAVE labor costs and materials

– other models on request / subject to modification and errors –

**CHARACTERISTICS AND SPECIAL FEATURES**

rustproof, stable suspension bracket

Fall- and impact-resistant polycarbonate housing, resistant to oil, acids, and alkaline solutions, self-extinguishing



**Dimensions:**

Diameter max. 248 mm  
Total height incl. bracket 299 mm

LED driver



Large neoprene ring press-fitted in a guide groove seals sprayproof



carrier plate



LED board, 20W, 2.320lm

Shock- and impact-resistant clear cover of satinised Makrolon



Locking ring of polycarbonate with 3 screws of stainless steel, undetachable

**REPLACEMENT PARTS:**

cover of satinised Makrolon  
Complete locking ring  
Neoprene ring

Order No.

**CX009**  
**CX001**  
**CX002**

**ACCESSORIES:**

Magnetic holder with strong gripping force and carabiner hook

Order No.

**KX/MAG**

– other models on request / subject to modification and errors –