

FIELDS OF APPLICATION:

- building and construction sites
- industry, trade, and commerce

- in the protection class 3 model, particularly suitable for use in narrow, conductive areas with limited freedom of movement (pressure vessels, filtration plants, pipelines, containers, shafts, vehicles, etc.)



VERSIONS:

Output	Cable	Accessories	Order No.		
			24 V AC	42 V AC	230 V AC
20 W	5 m	-	AL2420/5	AL4220/5	AL2320/5
	10 m	-	AL2420/10	AL4220/10	AL2320/10
	20 m	-	AL2420/20	AL4220/20	AL2320/20
20 W	5 m	Magnet	ML2420/5	ML4220/5	ML2320/5
	10 m	Magnet	ML2420/10	ML4220/10	ML2320/10
	20 m	Magnet	ML2420/20	ML4220/20	ML2320/20

– power supply cable INDUSTRIEFLEX® 07 HT–

SPECIAL FEATURES:

- LED panel with highly efficient SMD LEDs → LED panel with high light output, 2.320 lm, with low energy consumption
- colour temperature 5.700 K → similar to daylight
- Solid rubber housing with shock-proof Makrolon cover, satined → shock- and impact-resistant, long service life, even under tough operating conditions, **COST SAVINGS!**
- nylon clamping ring with hanging bracket → simple and safe mounting as hanging lamp
- with a clamp at the bottom → assembling on an scaffold support
- IP 54 → safety in use, splash-proof

REPLACEMENT PARTS:

satined Makrolon cover (upper part)

Order No.

A02/S

– other cable lengths and other models on request / subject to modification and errors –