



Configuration Example

Suspension and wall-mounted distribution boxes

Solid Rubber Housing
Series
TRIER

Number

Output

Sockets

Fuse
Protection or
Equipment

Residual Current
Circuit Breaker
RCD Type A

Entry
Screw Size

Order No.



8 sockets with earthing contact	8 B-Autom. 1p.	40A/30mA/4p.	M 25	2858001
12 sockets with earthing contact	12 B-Autom. 1p.	—	M 25	2848001



1 CEE 400V 32A 5p. and 1 CEE 400V 16A 5p. and 4 sockets with earthing contact	1 C-Autom. 3p. 1 C-Autom. 3p. 2 B-Autom. 1p.	63A/30mA/4p.	M 32	2858301
2 CEE 400V 16A 5p. and 4 sockets with earthing contact	2 C-Autom. 3p. 2 B-Autom. 1p.	63A/30mA/4p.	M 32	2858153



1 CEE 400V 32A 5p. and 1 CEE 400V 16A 5p. and 2 sockets with earthing contact	1 C-Aut. 3p. 1 C-Aut. 3p. 2 B-Aut. 1p.	63A/30mA/4p.	M 32	2858316
1 CEE 400V 32A 5p. and 1 CEE 400V 16A 5p. and 6 sockets with earthing contact	1 C-Autom. 3p. 1 C-Autom. 3p. 6 B-Autom. 1p.	—	M 32	2848301

– other models on request / subject to modification and errors –

Number	Output Sockets	Fuse Protection or Equipment	RCD Type A Residual Current I _n I _{Δn}	Entry Screw Size	Order No.
--------	----------------	------------------------------	--	------------------	-----------

1 CEE 400V 32A 5p. and 2 CEE 400V 16A 5p. and 2 sockets with earthing contact	1 C-Autom. 3p. 1 C-Autom. 3p. 2 B-Autom. 1p.	63A/30mA/4p.		M 32	2858374
1 CEE 400V 32A 5p. and 2 CEE 400V 16A 5p. and 2 sockets with earthing contact	1 C-Autom. 3p. 1 C-Autom. 3p. 2 B-Autom. 1p.	—		M 32	2848302



1 CEE 400V 63A 5p. and 1 CEE 400V 32A 5p. and 1 CEE 400V 16A 5p. and 2 sockets with earthing contact	— 1 C-Autom. 3p. 1 C-Autom. 3p. 2 B-Autom. 1p.	63A/30mA/4p.		M 32	2858601
---	---	--------------	--	------	----------------



4 CEE 400V 16A 5p.	4 C-Autom 3p.	—		M 32	2848125
4 CEE 400V 32A 5p.	4 C-Autom 3p.	—		M 32	2848303



– other models on request / subject to modification and errors –



- Lexan transparent hinged windows
 - V2A axis, 6 mm Ø
 - stainless-steel spring with high elastic force
 - with knurled-head screws on request

The solid rubber housing is produced using a press and vulcanization process. In combination with the special material employed, this allows us to achieve those qualities that set this distribution box apart.

Dimensions: H 380 mm, W 260 mm, D 150 mm

Special Features:

- over 600 already produced versions guarantee a custom-tailored solution on demand
 - interior space allows cross-sections to be connected (up to 35 mm²) and 2 cables to be laid (5 x 35 mm²) - feed and outgoing lines
 - 6 undetachable lid screws made of V2A steel allow the lid to be attached to the base tightly and securely
 - under the impact-resistant Lexan transparent hinged windows there is room for panel plugs and fuses up to max. 12 TE
 - protruding housing sections in the window area protect the window against mechanical damage
 - wall-mounted distribution boxes are available with a broad range of options: shafts, racks, tripods, and wall-mounted consoles; hot-dip galvanized, painted, or plastic-powder-coated; made of steel or V2A steel; various sizes and forms
- no compromises
PRACTICABILITY
 - the supply cables can be honed, which enables one to do without additional junction boxes
TIME AND COST SAVINGS
 - no-rust screws that can be loosened anytime -
MAINTENANCE FREE
 - measures for safeguarding people, devices, and cables as well as short-circuit protection all conform to valid regulations
SAFETY
 - no additional protective cover necessary
COST REDUCTION
 - **ENERGY ISLANDS** for all purposes and sites. Optimally suited for outdoor use as well.
LONG SERVICE LIFE guaranteed

ACCESSORIES:

- V2A wall-mounting brackets (pre-installed on request)