

Solid Rubber Housing
 Series
TRIER

| Number | Output | Sockets | Fuse Protection or Equipment | Residual Current | Circuit Breaker | RCD Type A | Entry | Screw Size | Order No. |
|--------|--------|---------|------------------------------|------------------|-----------------|------------|-------|------------|-----------|
|--------|--------|---------|------------------------------|------------------|-----------------|------------|-------|------------|-----------|



| | | | | |
|----------------------------------|-----------------|--------------|------|----------------|
| 8 sockets with earthing contact | 8 B-Autom. 1p. | 40A/30mA/4p. | M 25 | 2858001 |
| 12 sockets with earthing contact | 12 B-Autom. 1p. | — | M 25 | 2848001 |



| | | | | |
|---|--|--------------|------|----------------|
| 1 CEE 400V 32A 5p. and 1 CEE 400V 16A 5p. and 4 sockets with earthing contact | 1 C-Autom. 3p. 1 C-Autom. 3p. 2 B-Autom. 1p. | 63A/30mA/4p. | M 32 | 2858301 |
| 2 CEE 400V 16A 5p. and 4 sockets with earthing contact | 2 C-Autom. 3p. 2 B-Autom. 1p. | 63A/30mA/4p. | M 32 | 2858153 |



| | | | | |
|---|--|--------------|------|----------------|
| 1 CEE 400V 32A 5p. and 1 CEE 400V 16A 5p. and 2 sockets with earthing contact | 1 C-Aut. 3p. 1 C-Aut. 3p. 2 B-Aut. 1p. | 63A/30mA/4p. | M 32 | 2858316 |
| 1 CEE 400V 32A 5p. and 1 CEE 400V 16A 5p. and 6 sockets with earthing contact | 1 C-Autom. 3p. 1 C-Autom. 3p. 6 B-Autom. 1p. | — | M 32 | 2848301 |

— other models on request / subject to modification and errors —

| Number | Output | Sockets | Fuse Protection or Equipment | Residual Current I _n | RCD Type A | Entry | Screw Size | Order No. |
|--------|--------|---------|------------------------------|---------------------------------|------------|-------|------------|-----------|
|--------|--------|---------|------------------------------|---------------------------------|------------|-------|------------|-----------|

| | | | | | | | |
|---|--|--|--------------|--|------|--|----------------|
| 1 CEE 400V 32A 5p. and 2 CEE 400V 16A 5p. and 2 sockets with earthing contact | 1 C-Autom. 3p. 1 C-Autom. 3p. 2 B-Autom. 1p. | | 63A/30mA/4p. | | M 32 | | 2858374 |
| 1 CEE 400V 32A 5p. and 2 CEE 400V 16A 5p. and 2 sockets with earthing contact | 1 C-Autom. 3p. 2 C-Autom. 3p. 2 B-Autom. 1p. | | — | | M 32 | | 2848302 |



| | | | | | | | |
|--|---|--|--------------|--|------|--|----------------|
| 1 CEE 400V 63A 5p. and 1 CEE 400V 32A 5p. and 1 CEE 400V 16A 5p. and 2 sockets with earthing contact | — 1 C-Autom. 3p. 1 C-Autom. 3p. 2 B-Autom. 1p. | | 63A/30mA/4p. | | M 32 | | 2858601 |
|--|---|--|--------------|--|------|--|----------------|



| | | | | | | | |
|--------------------|---------------|--|---|--|------|--|----------------|
| 4 CEE 400V 16A 5p. | 4 C-Autom 3p. | | — | | M 32 | | 2848125 |
| 4 CEE 400V 32A 5p. | 4 C-Autom 3p. | | — | | M 32 | | 2848303 |



– other cable lengths and further models on request / subject to modification and errors –



Dimensions: H 380 mm, W 260 mm, D 150 mm



- Lexan transparent hinged windows
 - V2A axis, 6 mm Ø
 - stainless-steel spring with high elastic force
 - with knurled-head screws on request

The solid rubber housing is produced using a press and vulcanization process. In combination with the special material employed, this allows us to achieve those qualities that set this distribution box apart.

Special Features:

- over 600 already produced versions guarantee a custom-tailored solution on demand
- interior space allows cross-sections to be connected (up to 35 mm²) and 2 cables to be laid (5 x 35 mm²) - feed and outgoing lines
- 6 undetachable lid screws made of V2A steel allow the lid to be attached to the base tightly and securely
- under the impact-resistant Lexan transparent hinged windows there is room for panel plugs and fuses up to max. 12 TE
- protruding housing sections in the window area protect the window against mechanical damage
- wall-mounted distribution boxes are available with a broad range of options: shafts, racks, tripods, and wall-mounted consoles; hot-dip galvanized, painted, or plastic-powder-coated; made of steel or V2A steel; various sizes and forms

- no compromises
PRACTICABILITY
- the supply cables can be honed, which enables one to do without additional junction boxes
TIME AND COST SAVINGS
- no-rust screws that can be loosened anytime -
MAINTENANCE FREE
- measures for safeguarding people, devices, and cables as well as short-circuit protection all conform to valid regulations
SAFETY
- no additional protective cover necessary
COST REDUCTION
- **ENERGY ISLANDS** for all purposes and sites. Optimally suited for outdoor use as well.
LONG SERVICE LIFE guaranteed

ACCESSORIES:

- V2A wall-mounting brackets
(pre-installed on request)