


**MODELS:**

Lamp	Output	Luminous Flux LED Panel	Dimensions (H x Ø)	Weight	Cable with Plug	Order No. 24 V AC	Order No. 42 V AC	Order No. 230 V AC*
LED- Panel	200 W	28.100 lm	590 x 270 mm	9,7 kg	5 m 10 m	-	-	LTL23200/5 LTL23200/10
	180 W	25.250 lm	850 x 270 mm	13,1 kg	5 m 10 m	LTL24180/5 LTL24180/10	LTL42180/5 LTL42180/10	- -
	400 W	55.450 lm		13,4 kg	5 m 10 m	-	-	LTL23400/5 LTL23400/10

\* Smart Control on demand

**SPECIALS FEATURES:**

- mobile large area lighting
- fast setup and dismantling
- 3-phase-switch protected on the bottom side
- passive cooling (maintenance-free)
- impact protection from silicon-rubber edges
- housing of satined polycarbonate  
(Ø 250 mm without silicon edge protection)
- stands on the floor / tripod mounting / hanging
- IP 65
- vibration-proof according to DIN EN 60598-1
- cables of INDUSTRIEFLEX® 07 HT
- Smart Control for 230 V model on demand
- simple transport
- immediately usable
- I = one-sided (50%)  
0 = OFF  
II = all-round (100%)
- dissipates heat in the interior via aluminum body
- impact- and break-proof construction
- low wind load as a result of the cylindrical shape
- tripod connection for DIN pin (30 mm DIN 14640)
- dust and water proof
- suitable for rough operating conditions
- for special features visit [www.elspro.de/en](http://www.elspro.de/en)
- intelligent remote control for LUMITOWER LED II via mobile app from a mobile phone or tablet

- other cable lengths and models on request / subject to modifications and errors -

## ELSPRO LUMITOWER LED II



### APPLICATIONS

#### Authorities and organizations with security tasks

- accident reports
- crime scene lighting
- fire investigations
- disaster operation

#### Industry / Handwork

- construction site lighting
- power plant inspections
- space illumination
- track bed illumination

#### Outdoor events

- sporting events
- film/theater

### ACCESSORIES:

**Tripod** (detailed information on pages 7-9)



Order No. **TW7840SA**  
Type THW (S. 13.1)  
H 480 cm



Type IFW 2.0 (S. 13.2.1)  
**TV7845SA**  
H 415 cm



Type BETA 3 (S. 13.3)  
**TV7521SA**  
H 252 cm



Webbing incl. snap hook  
**LTL005**

– other cable lengths and models on request / subject to modifications and errors –