



LYWF-300XL with optional stainless steel support frame

VERSIONS:


Voltage Input	Illuminant	Lumen	Cable	Order No.	
				without frame	with frame
230 V AC	36 pcs High-Power-LED	6,378 lm	without	LYWF-300H/-	-
			10 m SL07HT 3 G 2.5 mm ²	-	LYWF-300HG/10

- device connecting cables INDUSTRIEFLEX® 07 HT -

- + The version with supply cable is optionally available with a steel or CEAG plug on the input side upon request.
- + The 230 V version is optionally available with 1 steel or CEAG built-in socket on the rear output side upon request.

FEATURES AND CHARACTERISTICS:

- Robust aluminum housing, plastic powder-coated
- Hardened glass lens
- 2 independent modules with 18 LEDs each
- Explosion-proof:
 - Ex II 2 G D Ex eb mb op is IIC T4 Gb
 - Ex tb op is IIIC T118°C Db T= -40°C bis +55°C
- Protection class IP 66/67
- Ambient temperature -40 bis +55 °C
- Dimensions housing (DxWxH) approx. 370x280x480 mm
- Weight (without rack/cable) 5.50 kg
- Optional frame and protective grille made of stainless steel
The version without frame is supplied with mounting bracket for assembly.
- Indication function (flashing mode) as soon as the lamp is not operated within the permissible voltage range.
- Lifetime \geq 100.000 operating hours



- other models on request / subject to modification and error -



magnet set LYWF-545



safety mesh LYWF-480



scaffold attachment kit LYWF-699

COMPONENTS AND ACCESSORIES:	Order-No.
Tripod medium for LYWF-300XL	LYLL-699
Tripod heavy for LYWF-300XL	LYLL-668
"Z" bracket and bolts for tripods LYLL-668 and LYLL-699	LYLL-669
safety mesh made of V2A steel for LYWF-300XL*	LYWF-480
Magnet set (4 pcs magnets) for LYWF-300XL*	LYWF-545
Scaffold attachment kit for LYWF-300XL*	LYWF-699
Front protective cover 1 piece for LYWF-300XL	LYWF-421
Front protective cover 3 pieces for LYWF-300XL	LYWF-421/3

* Attention: to be used for versions **with frame** only