

Safety Transformers

from 120VA-4500VA



Mobile Protection Class 2



Volt-Ampere
Power

Input*
Voltage ~

Output
Voltage ~

No.

Sockets
Output

Input



Output



Order No.

CE **K2**
Solid Rubber Housing
Series

120 VA	230V	24V	CEE 24V 16A 2p.	0,5A	—	3080101
120 VA	230V	42V	CEE 42V 16A 2p.	0,5A	—	3080102



160 VA	230V	24V	1 CEE 24V 16A 2p.	0,7A	—	3380170
160 VA	230V	24V	2 CEE 24V 16A 2p.	0,7A	—	3380185
350 VA	230V	24V	1 CEE 24V 16A 2p.	1,5A	—	3380186
350 VA	230V	24V	2 CEE 24V 16A 2p.	1,5A	—	3380165



160 VA	230V	42V	1 CEE 42V 16A 2p.	0,7A	—	3380183
160 VA	230V	42V	2 CEE 42V 16A 2p.	0,7A	—	3380171
350 VA	230V	42V	1 CEE 42V 16A 2p.	1,5A	—	3380169
350 VA	230V	42V	2 CEE 42V 16A 2p.	1,5A	—	3380182



500 VA	230V	24V	2 CEE 24V 16A 2p.	2,0A	2 Neozed 1p.	3480101
750 VA	230V	24V	3 CEE 24V 16A 2p.	3,0A	3 Neozed 1p.	3480102
1000 VA	230V	24V	4 CEE 24V 16A 2p.	4,0A	4 Neozed 1p.	3480103
500 VA	230V	42V	2 CEE 42V 16A 2p.	2,0A	—	3480104
750 VA	230V	42V	3 CEE 42V 16A 2p.	3,0A	—	3480105
1000 VA	230V	42V	4 CEE 42V 16A 2p.	4,0A	2 Neozed 1p.	3480106



1500 VA ¹⁾	230V	24V	4 CEE 24V 16A 2p.	6,0A	4 Neozed 1p.	3980105
2000 VA ¹⁾	230V	24V	6 CEE 24V 16A 2p.	8,0A	6 Neozed 1p.	3980101
2500 VA ¹⁾	230V	24V	6 CEE 24V 16A 2p.	10,0A	6 Neozed 1p.	3980102
1500 VA ¹⁾	230V	42V	4 CEE 42V 16A 2p.	6,0A	4 Neozed 1p.	3980106
2000 VA ¹⁾	230V	42V	6 CEE 42V 16A 2p.	8,0A	6 Neozed 1p.	3980103
2500 VA ¹⁾	230V	42V	6 CEE 42V 16A 2p.	10,0A	6 Neozed 1p.	3980104



3 m feed line with contour plug
1) inrush current limiter

– other models on request / subject to modification and errors –



CE **K2**
Solid Rubber Housing
 Series NURNBERG

Volt-Ampere Power	Input* Voltage ~	Output Output	Sockets Output	Input 	Output 	Order No.
----------------------	---------------------	------------------	-------------------	-----------	------------	-----------



3000 VA	230V	24V	10 CEE 16A 2p.	13A	10 B-Autom. 1p.	3640101
---------	------	-----	----------------	-----	-----------------	----------------

4000 VA	230V	24V	10 CEE 16A 2p.	16A	10 B-Autom. 1p.	3640109
---------	------	-----	----------------	-----	-----------------	----------------



3000 VA	230V	24V	10 CEE 16A 2p.	13A	10 B-Autom. 1p.	3640102
---------	------	-----	----------------	-----	-----------------	----------------

4000 VA	230V	24V	10 CEE 16A 2p.	16A	10 B-Autom. 1p.	3640110
---------	------	-----	----------------	-----	-----------------	----------------

all models with inrush current limiter



Profile:

- 2 large carrying handles with full-length steel reinforcement ensure secure transport and allow the unit to be carried by 2 people
- the frontal array guarantees unimpeded access to all sockets, even when high in number
- in the distribution box interior, carrier elements and lateral rods ensure necessary support for the heavy transformers
- all fixtures are smoothly and easily accessible by a specialized electrician for on-demand maintenance
- all one-phase transformers are equipped with an inrush current limiter in order to avoid inadvertent tripping of the mains fuse (e.g., B automats)
- an added heat protection tube (H07 V-K for all insulated wires) permanently rules out isolation errors and short circuits in the wiring
- a broad number of different transport carts counts among the available accessories
- further outstanding features and qualities distinguish the ELSPRO safety and isolation transformers and guarantee high quality and safety standards