

Solid Rubber Housing  
Series

Power	Volt-Ampere	Input* Voltage ~	Output	Sockets	Cable Length Meters	Cross-Section mm <sup>2</sup>	Light Type	Order No.
-------	-------------	---------------------	--------	---------	---------------------------	----------------------------------	------------	-----------



LRX



LRX



\*\* cable gland M20

50 VA	230 V*	24 V	0,2 A	30	2 x 2,5	HSW <sup>1</sup>	<b>3X80903</b>	
		42 V					on request	
50 VA	230 V*	24 V	0,2 A	30	2 x 2,5	QS <sup>2</sup>	<b>3X80905</b>	
		42 V					on request	

\* 3 m special line INDUSTRIEFLEx® 07 HT 2 x 1,0 mm<sup>2</sup> with contour plug

50 VA	230 V**	24 V	0,2 A	30	2 x 2,5	HSW <sup>1</sup>	<b>3X88910</b>	
		42 V				QS <sup>2</sup>	on request	

The power cable is firmly connected.

With easily removable illuminated lamp!

The safety transformer is laterally flange-mounted.

Safety extra low voltage of 24 V is conducted through collector rings.

1 = solid rubber handheld led lamp	9 W	24 V	HSW LED (page 21.11)	
2 = inspection lamp	20 W	24 V	QS (page 21.21)	

– other models on request / subject to modification and errors –