

Isolation Transformers

from 120VA-4500VA

Mobile Protection Class 2

CE    **K2**
Solid Rubber Housing
 Series

Volt-Ampere Power	Input* Voltage ~	Output Voltage ~	No.	Sockets Output	Input	Output	Order No.
----------------------	---------------------	---------------------	-----	-------------------	-------	--------	-----------

120 VA	230V	230V		1 socket with earthing contact -without  -			3080001
--------	------	------	--	--	---	---	----------------












125 VA	230V	230V		1 socket with earthing contact -without  -			3380006
--------	------	------	--	--	---	---	----------------












350 VA	230V	230V		1 socket with earthing contact -without  -			3380005
--------	------	------	--	--	---	---	----------------



500 VA	230V	230V		1 socket with earthing contact -without  -			3480001
750 VA	230V	230V		1 socket with earthing contact -without  -			3480002
1000 VA	230V	230V		1 socket with earthing contact -without  -			3480003



1500 VA ¹⁾	230V	230V		1 socket with earthing contact -without  -			3980003
2000 VA ¹⁾	230V	230V		1 socket with earthing contact -without  -			3980001
2500 VA ¹⁾	230V	230V		1 socket with earthing contact -without  -			3980002



– other models on request / subject to modification and errors –

* 3 m feed line with contour plug
¹⁾ inrush current limiter

**Solid Rubber Housing**
Series NURNBERG

Volt-Ampere Power	Input* Voltage ~	Output Output	Sockets Output	Input 	Output 	Order No.
----------------------	---------------------	------------------	-------------------	-----------	------------	-----------



3000 VA	1) 230V	230V	1 socket with earthing contact —without	13A	—	3680005
3500 VA	1) 230V	230V	1 socket with earthing contact —without	15A	—	3680001
4000 VA	1) 230V	230V	1 socket with earthing contact —without	16A	—	3680002



4000 VA	2) 400V 3~	400V 3~	1 CEE 400V 3~ 16A	6A 3p.	—	3681101
4500 VA	2) 400V 3~	400V 3~	1 CEE 400V 3~ 16A	6A 3p.	—	3681102

**Profile of Order No. 5691003**

Mobile isolation transformer in an ELSPRO solid rubber distribution box on a trolley from the NÜRNBERG series

Input: 3 m cable INDUSTRIEFLEX® 07 with CEE plug 5 x 16 A/400 V

Fixtures: 1 three-phase transformer with 3 separate output windings

Primary power: 4500 VA, 3x400 V

Second power: 3x1500 VA, 3x230 V single-phase

Switching group: Diii Nominal frequency: 50-60 Hz

- primary safeguarding via a motor protection switch 6 A/3-pol.

Output: 3 sockets with earthing contact; also secured without earthing contact by way of 3 MCB 6 A/1 pol. in B type

- each with an engraved caution sign:

ATTENTION!

Connect only 1 consumer to each earthing contact socket!

Model Features:

- K2 type
- highly insulated
- the circuit breakers are externally accessible and are situated behind 2 transparent hinged windows for protection
- the steel frame of the trolley features a plastic powder coating
- 2 ball-bearing-mounted solid rubber tires, 200 mm in diameter
- compact structural shape and favorable center of gravity
- transformer according to VDE 0570
- splashproof

1) 3 m feed line with contour plug
2) 3 m feed line with CEE plug, 400 V 16 A 5p.