

Polyurethane Device Connecting Cables ELSPRO-FLEX® G05/G07

Special hose line with modified polyurethane sheath and EPR lead insulation

RANGE OF APPLICATION:

- construction and assembly sites
- industry, trade, and agriculture
- cable certified by VDE and HAR
- tin-plated CU conductor
- signal color yellow
- type code printed on external sheath

MODEL:

- with molded contour plug and 2-lead cable
- with molded earthed plug and 3-lead cable
- sheath has been removed from the end, while leads have been insulated and fitted with end ferrules



SPECIAL FEATURES:

- ULTRA-FINE copper (highly flexible) → significantly lower chance of “lead rupture”; easy handling, even under rough conditions
- ergonomic and anti-slip plug form → easy plugging and unplugging
- ready to use; featuring extended protective earthing conductor (3-lead) → COST SAVINGS THANKS TO MINIMIZED INSTALLATION TIME
- largely UV- and ozone-resistant → longer service life in outdoor areas

Technical data and other specifics pertaining to the ELSPRO-FLEX® G cable can be found on pages 8.9 + 8.10

Length	Cross-Section	Outside Ø ca.	Plug Type	Order No.
3 m 5 m	2 x 1.0 mm ² 2 x 1.0 mm ²	7.1 mm	contour plug	210 M3 G05 210 M5 G05
3 m 5 m	2 x 1.5 mm ² 2 x 1.5 mm ²	8.7 mm	contour plug	215 M3 G07 215 M5 G07
3 m 5 m	3 G 1.5 mm ² 3 G 1.5 mm ²	9.2 mm	earthed plug	315 M3 G07 315 M5 G07

– other models on request / subject to modification and errors –