Polyurethane Device Connecting Cables ELSPRO-FLEX® G05/G07

Special hose line with modified polyurethane sheath and EPR lead insulation

RANGE OF APPLICATION:

- construction and assembly sites
- industry, trade, and agriculture

- cable certified by VDE and HAR
- tin-plated CU conductor
- signal color yellow
- type code printed on external sheath

MODEL:

- with molded contour plug and 2-lead cable
- with molded earthed plug and 3-lead cable
- sheath has been removed from the end, while leads have been insulated and fitted with end ferrules

SPECIAL FEATURES:

- ULTRA-FINE copper (highly flexible)
  → significantly lower chance of “lead rupture”; easy handling, even under rough conditions
- ergonomic and anti-slip plug form
  → easy plugging and unplugging
- ready to use; featuring extended protective earthing conductor (3-lead)
  → COST SAVINGS THANKS TO MINIMIZED INSTALLATION TIME
- largely UV- and ozone-resistant
  → longer service life in outdoor areas

Technical data and other specifics pertaining to the ELSPRO-FLEX® G cable can be found on pages 8.9 + 8.10

Length	Cross-Section	Outside ∅ ca.	Plug Type	Order No.
3 m 5 m	2 x 1.0 mm² 2 x 1.0 mm²	7.1 mm	contour plug	**210 M3 G05** **210 M5 G05**
3 m 5 m	2 x 1.5 mm² 2 x 1.5 mm²	8.7 mm	contour plug	**215 M3 G07** **215 M5 G07**
3 m 5 m	3 G 1.5 mm² 3 G 1.5 mm²	9.2 mm	earthed plug	**315 M3 G07** **315 M5 G07**

– other models on request / subject to modification and errors –

ELSPRO Elektrotechnik GmbH & Co. KG
Kleinhülsen 47 · 40721 Hilden · Germany
+49 (0) 21 03 / 97 10 - 45
+49 (0) 21 03 / 97 10 - 80
sales@elspro.de
www.elspro.de/en/