ELSPRO-FLEX® WL 05 (from 2 x 0.75 - 5 G 1.00 mm²)
ELSPRO-FLEX® WL 07 (from 2 x 1.5 - 7 G 2.5 mm²)
SPIRAL CABLE

FIELDS OF APPLICATION:

- tambour doors, hydraulic ramps, electrical tools, portable equipment, etc.
- *indoors and outdoors*

Special hose line with modified polyurethane sheath

- signal color orange
- type code printed on external sheath

NOMINAL VOLTAGE:
– WL 05 U◦/U = 300/500 V
– WL 07 U◦/U = 450/750 V

OPERATING VOLTAGE:
– WL 05 U◦/U = 330/570 V
– WL 07 U◦/U = 500/865 V

TEMPERATURE RANGE:
- flexible -30°C / +90°C
(conductor temperature)

SPECIAL FEATURES:

• custom-tailored to your needs starting at just 3 cables	→ no need to store large amounts of material
• block lengths, extended lengths, and stretched ends can be adapted individually	→ optimized use during each application
• extremely high restoring force thanks to state-of-the-art winding technology	→ long-term restorative effect
• sheath withstands high mechanical loads and is notch ductile and abrasion-resistant	→ long service life, fewer production losses COST SAVINGS
• resistant to grease, organic and inorganic oils	→ next to no “swelling” of the cable

SEVERAL EXAMPLES: (with both ends straight, each 20 cm in length)

Cross-Section	Block Length	Extended Length	Order No.
2 x 1.0 mm²	80 cm	320 cm	**WL08210**
	120 cm	480 cm	**WL12210**
	260 cm	1040 cm	**WL26210**
2 x 1.5 mm²	80 cm	320 cm	**WL08215**
	120 cm	480 cm	**WL12215**
	260 cm	1040 cm	**WL26215**
3 G 1.5 mm²	80 cm	320 cm	**WL08315**
	120 cm	480 cm	**WL12315**
	260 cm	1040 cm	**WL26315**
5 G 1.0 mm²	80 cm	320 cm	**WL08510**
	120 cm	480 cm	**WL12510**
	260 cm	1040 cm	**WL26510**
5 G 1.5 mm²	80 cm	320 cm	**WL08515**
	120 cm	480 cm	**WL12515**
	260 cm	1040 cm	**WL26515**

– other models on request / subject to modification and errors –

ELSPRO Elektrotechnik GmbH & Co. KG
Kleinhülsen 47 · 40721 Hilden · Germany
+49 (0) 21 03 / 97 10 - 45
+49 (0) 21 03 / 97 10 - 80
sales@elspro.de
www.elspro.de/en/