

**ELSPRO-FLEX® WL 05** (from 2 x 0.75 - 5 G 1.00 mm<sup>2</sup>) **SPIRAL CABLE**  
**ELSPRO-FLEX® WL 07** (from 2 x 1.5 - 7 G 2.5 mm<sup>2</sup>)

**FIELDS OF APPLICATION:**

- tambour doors, hydraulic ramps, electrical tools, portable equipment, etc.
- *indoors and outdoors*

**Special hose line with modified polyurethane sheath**

- signal color orange
- type code printed on external sheath



**NOMINAL VOLTAGE:**

- WL 05 U<sub>0</sub>/U = 300/500 V
- WL 07 U<sub>0</sub>/U = 450/750 V

**OPERATING VOLTAGE:**

- WL 05 U<sub>0</sub>/U = 330/570 V
- WL 07 U<sub>0</sub>/U = 500/865 V

**TEMPERATURE RANGE:**

– flexible -30°C / +90°C  
 (conductor temperature)

**SPECIAL FEATURES:**

- custom-tailored to your needs starting at just 3 cables → no need to store large amounts of material
  - block lengths, extended lengths, and stretched ends can be adapted individually → optimized use during each application
  - extremely high restoring force thanks to state-of-the-art winding technology → long-term restorative effect
  - sheath withstands high mechanical loads and is notch ductile and abrasion-resistant → long service life, fewer production losses
  - resistant to grease, organic and inorganic oils → next to no “swelling” of the cable
- COST SAVINGS**

**SEVERAL EXAMPLES:** (with both ends straight, each 20 cm in length)

Cross-Section	Block Length	Extended Length	Order No.
2 x 1.0 mm <sup>2</sup>	80 cm	320 cm	<b>WL08210</b>
	120 cm	480 cm	<b>WL12210</b>
	260 cm	1040 cm	<b>WL26210</b>
2 x 1.5 mm <sup>2</sup>	80 cm	320 cm	<b>WL08215</b>
	120 cm	480 cm	<b>WL12215</b>
	260 cm	1040 cm	<b>WL26215</b>
3 G 1.5 mm <sup>2</sup>	80 cm	320 cm	<b>WL08315</b>
	120 cm	480 cm	<b>WL12315</b>
	260 cm	1040 cm	<b>WL26315</b>
5 G 1.0 mm <sup>2</sup>	80 cm	320 cm	<b>WL08510</b>
	120 cm	480 cm	<b>WL12510</b>
	260 cm	1040 cm	<b>WL26510</b>
5 G 1.5 mm <sup>2</sup>	80 cm	320 cm	<b>WL08515</b>
	120 cm	480 cm	<b>WL12515</b>
	260 cm	1040 cm	<b>WL26515</b>

– other models on request / subject to modification and errors –