

Plug

Cable

Length

Meter

mm²
Cross-Section

Connector

Order No.

CE ⚠ ⚡ K2

solid rubber earthing con- tact with hinged lid 16 A / 3 p.	5	3 G 1,5	solid rubber earthing con- tact 16 A / 3 p.	S5K/PG
	10			S10K/PG
	20			S20K/PG
<i>voltage indica- tor optional</i>	5	3 G 2,5		S5.2K/PG
	10		S10.2K/PG	
	20		S20.2K/PG	



triple earthing contact with hinged lids and voltage indicator 16 A / 3 p.	5	3 G 1,5	solid rubber earthing con- tact 16 A / 3 p.	S5KD/PG
	10			S10KD/PG
	20			S20KD/PG
	5	3 G 2,5		S5.2KD/PG
	10			S10.2KD/PG
	20			S20.2KD/PG



CEE 230 V 16 A / 3 p.	5	3 G 1,5	CEE 230 V 16 A / 3 p.	CS5K2213
	10			CS10K2213
	20			CS20K2213
	5	3 G 2,5		CS5.2K2213
	10			CS10.2K2213
	20			CS20.2K2213



CEE 400 V 16 A / 5 p.	5	5 G 1,5	CEE 400 V 16 A / 5 p.	CS5K1
	10			CS10K1
	20			CS20K1
	5	5 G 2,5	<i>with phase inverter plug on request</i>	CS5.2K1
	10			CS10.2K1
	20			CS20.2K1



CEE 400 V 32 A / 5 p.	5	5 G 4,0	CEE 400 V 32 A / 5 p. <i>with phase inverter plug on request</i>	CS5K3
	10			CS10K3
	20			CS20K3



CEE 400 V 63 A / 5 p.	5	5 G 16,0	CEE 400 V 63 A / 5 p.	CS5K6
	10			CS10K6
	20			CS20K6



Technical data and other special features of the INDUSTRIEFLEX® 07 HT cable used
as well as further configuration options can be found on the back and on pages 8.1 + 8.2

– other models on request / subject to modification and errors –

Extension Cables with INDUSTRIEFLEX® 07 HT



MODELS:

- any desired length
- all customary connection systems
- partially customized solutions also possible
- multipole connector systems in all sizes (pages 7.0-7.5)
- other cross-sections
- other cable types on request
- K2 marking
- signal colour yellow
- ownership imprint possible



triple earthing
contact connector
with hinged lids and
voltage indicator



solid rubber
earthing contact
with hinged lid
(voltage indicator
optional)

SPECIAL FEATURES:

- **Cable INDUSTRIEFLEX® 07 HT**
heavy-duty rubber special hose lines that are waterproof and heat-resistant
 - modified external sheath mixture
 - cross-linked and compressed external sheathing material
 - FINE or ULTRA-FINE copper (copper class 6/5) (see page 8.2)
 - type designation H07RN-F, H07BN4-F und H07RN8-F
 - high-quality plug connectors with earthing contact displaying VDE, hammer
 - CEE plug connectors made of polyamide 6
 - tin-plated copper wires / inner leads
 - silicon-free sheath and lead insulation
 - made and tested by specialized professionals
- VDE 0285-525-2-21 / DIN EN 50525-2-21
 - oil, acid and UV resistant, flame retardant and self-extinguishing
 - mechanically extremely resilient, durable and tear-resistant
 - highly flexible - considerably lower chance of conductor breakage, easy handling even under difficult conditions
 - three lines combined in one
 - extremely robust, for permanent outdoor use
 - long service life even under extreme conditions, **COST SAVINGS**
 - no corrosion and no scaling of the connection points
 - no paint wetting
 - cables ready to use immediately

– other models on request / subject to modification and errors –

Selection of our cables always adheres to the VDE regulations valid at the present time.