For portable devices, electric tools, handheld units, etc.

RANGE OF APPLICATION:

- construction and assembly sites
- industry, trade, and agriculture
- special rubber cable
- signal color yellow
- tin-plated inside wiring
- internal marker threads
- type code printed on external sheath



MODEL:

- with molded contour plug and 2-lead cable
- with molded earthed plug and 3-lead cable
- sheath has been removed from the end, while leads have been insulated and fitted with end ferrules

SPECIAL FEATURES:

- ergonomic and anti-slip plug form
- ready to use; featuring extended protective earthing conductor (3-lead)
- ultra-fine copper wire (highly flexible)
- → minimized installation time COST SAVINGS
- \rightarrow $% \left(a_{1}^{2}\right) =0$ easy handling, even under rough conditions

Length	Cross-Section	Outside ∅ ca.	Plug Type	Order No.
2 m 3 m 5 m 10 m	2 x 1.0 mm ²	8.2 mm	contour plug	210 M2 SL07 210 M3 SL07 210 M5 SL07 210 M10 SL07
2 m 3 m 5 m 10 m	2 x 1.5 mm²	9.1 mm	contour plug	215 M2 SL07 215 M3 SL07 215 M5 SL07 215 M10 SL07
2 m 3 m 5 m 10 m	3 G 1.5 mm ²	9.8 mm	earthed plug	315 M2 SL07 315 M3 SL07 315 M5 SL07 315 M10 SL07

Technical data and other specifics pertaining to the INDUSTRIEFLEX $^{\mbox{\scriptsize R}}$ HT cable can be found on pages 8.1 + 8.2

- other models on request / subject to modification and errors -

