

Device Connecting Cables INDUSTRIEFLEX® 05 HT

For hand-operated electrical equipment

- special rubber cable
- signal color yellow
- tin-plated inside wiring
- internal marker threads
- type code printed on external sheath



*** with small outside diameter ***

RANGE OF APPLICATION:

- permissible at construction and assembly sites for up to 4 m in length, provided that no other supplementary DIN/VDE regulations apply (e.g., 0740)

MODEL:

- with molded contour plug and 2-lead cable
- with molded earthed plug and 3-lead cable
- sheath has been removed from the end, while leads have been insulated and fitted with end ferrules

SPECIAL FEATURES:

- small outside diameter → effortless installation, even in the case of small device entry
- ergonomic and anti-slip plug form → easy plugging and unplugging
- ready to use; featuring extended protective earthing conductor (3-lead) → minimized installation time - COST SAVINGS
- ultra-fine copper wire (highly flexible) → easy handling, even under rough conditions

Technical data and other specifics pertaining to the INDUSTRIEFLEX® 05 HT cable can be found on page 8.8

Length	Cross-Section	Exterior \varnothing ca.	Plug Type	Order No.
4 m	2 x 1.0 mm ²	6.8 mm	contour plug	210M4IF
4 m	3 G 1.0 mm ²	7.2 mm	earthed plug	310M4IF

– other models on request / subject to modification and errors –